

PART NUMBER	ENCL	IMPEDANCE	HORSE POWER	NEC AMPS	MAX CONTINUOUS AMPS	HEIGHT	WIDTH	DEPTH	TERM TYPE	TERM TORQUE	TORQUE UM	TEMP RISE	WATTS LOSS	WEIGHT
KDRMA1H1	Open	HZ	0.25	0.7	1.4	3.63	4.45	1.78	TB	9	LB-IN	135	7.9	1.30
KDRMA2H1	Open	HZ	0.33	0.8	1.4	3.63	4.45	1.78	TB	9	LB-IN	135	9.2	1.50
KDRMA3H1	Open	HZ	0.5	1.1	1.6	3.63	4.45	1.78	TB	9	LB-IN	135	14.3	1.30
KDRMA4H1	Open	HZ	0.75	1.6	2.1	3.63	4.45	1.78	TB	9	LB-IN	135	19.3	1.40
KDRMA5H1	Open	HZ	1	2.1	2.3	3.63	4.45	1.78	TB	9	LB-IN	135	26.7	1.40
KDRMA6H1	Open	HZ	1.5	3	3.6	3.63	4.45	1.78	TB	9	LB-IN	135	30	1.60
KDRAA1H2	Open	HZ	2	3.4	3.8	4.44	4.25	2.64	TB	9	LB-IN	135	45	2.80
KDRAA2H2	Open	HZ	3	4.8	5.4	4.44	4.25	2.64	TB	9	LB-IN	135	41.8	3.00
KDRAA6H2	Open	HZ	4	6.2	7.6	4.44	4.25	2.64	TB	9	LB-IN	135	50.2	3.40
KDRAA3H2	Open	HZ	5	7.6	8.2	4.44	4.25	2.64	TB	9	LB-IN	135	80	3.70
KDRA4H	Open	HZ	7.5	11	12	4	4.18	3.75	TB	10	LB-IN	135	77	5.00
KDRA5H	Open	HZ	10	14	14	4	4.18	3.75	TB	10	LB-IN	135	111	5.00
KDRB2H	Open	HZ	15	21	27	5	6	4	TB	20	LB-IN	135	133	7.00
KDRC3H	Open	HZ	20	27	27	5.75	7.2	5	TB	20	LB-IN	135	108	15.00
KDRC1H	Open	HZ	25	34	35	5.75	7.2	5	TB	20	LB-IN	135	112	15.00
KDRE2H	Open	HZ	30	40	45	5.75	7.2	5	TB	20	LB-IN	135	141	16.00
KDRF4H	Open	HZ	40	52	60	7	9	6	TB	35	LB-IN	135	169	25.00
KDRF1H	Open	HZ	50	65	85	7	9	6	TB	35	LB-IN	115	191	25.00
KDRF2H	Open	HZ	60	77	77	7	9	6	TB	35	LB-IN	115	226	25.00
KDRH2H	Open	HZ	75	96	100	8.31	10.5	6	CB	120	LB-IN	115	212	45.00
KDRI2H	Open	HZ	100	124	125	8.5	10.5	6.31	CB	120	LB-IN	155	362	50.00
KDRG3H	Open	HZ	125	156	160	10.15	10.75	7.31	CB	275	LB-IN	155	274	55.00
KDRG1H	Open	HZ	150	180	185	10.15	11.38	8.25	CB	275	LB-IN	155	359	55.00
KDRJ1H	Open	HZ	200	240	240	10	10.88	9	CB	500	LB-IN	155	420	70.00
KDRL1H	Open	HZ	250	302	310	12.75	14.75	9.25	CB	275	LB-IN	155	548	110.00
KDRL2H	Open	HZ	300	361	365	12.75	14.75	9.25	CB	275	LB-IN	155	786	95.00
KDRL3H	Open	HZ	350	414	435	12.75	14.75	9.25	CB	275	LB-IN	155	750	100.00
KDRL4H	Open	HZ	400	477	480	12.75	14.75	9.25	CB	500	LB-IN	155	730	110.00
KDRL5H	Open	HZ	450	515	540	12.75	15.5	11.75	CB	500	LB-IN	155	774	120.00
KDRL6H	Open	HZ	500	590	590	12.75	15.5	11.75	CB	500	LB-IN	155	697	120.00
KDRS1H	Open	HZ	600	720	750	12.75	15.65	12.75	CB	500	LB-IN	155	1246	260.00
KDRS2H	Open	HZ	700	840	840	12.75	15.75	14.25	CB	500	LB-IN	155	1454	280.00
KDRX2H	Open	HZ	800	960	965	18.31	18	13	CB	375	LB-IN	115	1661	290.00
KDRX3H	Open	HZ	900	1080	1100	18.5	18	14.5	CB	375	LB-IN	115	1869	290.00
KDRX4H	Open	HZ	1000	1200	1200	18.5	18	14.5	CB	375	LB-IN	155	1337	300.00
KDRY2H	Open	HZ	1100	1320	1320	21.5	21	16.25	CB	375	LB-IN	115	2284	525.00
KDRY1H	Open	HZ	1250	1500	1500	21.5	21	16.25	CB	375	LB-IN	155	2596	695.00

\*Ratings and dimensions are equivalent to Part Numbers containing "UL"