

PART NUMBER	ENCL	IMPEDANCE	HORSE POWER	NEC AMPS	MAX CONTINUOUS AMPS	HEIGHT	WIDTH	DEPTH	TERM TYPE	TERM TORQUE	TORQUE UM	TEMP RISE	WATTS LOSS	WEIGHT
KDRMA1L1	Open	LZ	0.25	0.7	1.4	3.63	4.45	1.78	TB	9	LB-IN	135	5	1.30
KDRMA2L1	Open	LZ	0.33	0.8	1.7	3.63	4.45	1.78	TB	9	LB-IN	135	6.2	1.30
KDRMA3L1	Open	LZ	0.5	1.1	1.6	3.63	4.45	1.78	TB	9	LB-IN	135	9.7	1.30
KDRMA4L1	Open	LZ	0.75	1.6	2.3	3.63	4.45	1.78	TB	9	LB-IN	135	12.1	1.30
KDRMA5L1	Open	LZ	1	2.1	2.3	3.63	4.45	1.78	TB	9	LB-IN	135	25.2	1.20
KDRMA6L1	Open	LZ	1.5	3	3.4	3.63	4.45	1.78	TB	9	LB-IN	135	26.4	1.40
KDRMA7L1	Open	LZ	2	3.4	4.2	3.63	4.45	1.78	TB	9	LB-IN	135	23.5	1.40
KDRMA8L1	Open	LZ	3	4.8	5	3.63	4.45	1.78	TB	9	LB-IN	135	30.6	1.40
KDRAA6L2	Open	LZ	4	6.2	7.6	4.44	4.25	2.64	TB	9	LB-IN	135	39.2	3.00
KDRAA3L2	Open	LZ	5	7.6	8.2	4.44	4.25	2.64	TB	9	LB-IN	135	48.8	3.00
KDRAA4L2	Open	LZ	7.5	11	11	4.44	4.25	2.64	TB	9	LB-IN	135	62.9	3.20
KDRA5L	Open	LZ	10	14	14	4	4.18	3.75	TB	10	LB-IN	135	64	5.00
KDRB2L	Open	LZ	15	21	30	5	6	4	TB	20	LB-IN	135	65	8.00
KDRB1L	Open	LZ	20	27	30	5	6	4	TB	20	LB-IN	135	79	8.00
KDRD1L	Open	LZ	25	34	50	5.75	7.2	4.25	TB	20	LB-IN	135	96	10.00
KDRD2L	Open	LZ	30	40	45	5.75	7.2	4.25	TB	20	LB-IN	135	105	10.00
KDRC1L	Open	LZ	40	52	55	5.75	7.2	5	TB	20	LB-IN	135	114	15.00
KDRF2L	Open	LZ	50	65	65	7	9	6	TB	35	LB-IN	135	114	25.00
KDRF4L	Open	LZ	60	77	77	7	9	6	TB	35	LB-IN	135	169	25.00
KDRF3L	Open	LZ	75	96	110	7	9	6	CB	120	LB-IN	115	193	30.00
KDRH3L	Open	LZ	100	124	150	8.31	10.5	6	CB	275	LB-IN	115	225	40.00
KDRH2L	Open	LZ	125	156	165	8.31	10.5	6	CB	275	LB-IN	115	254	40.00
KDRH1L	Open	LZ	150	180	185	8.31	10.5	6	CB	275	LB-IN	115	299	40.00
KDRG3L	Open	LZ	200	240	240	10.15	11.38	8.25	CB	500	LB-IN	155	280	65.00
KDRG1L	Open	LZ	250	302	340	10.15	11.38	8.5	CB	275	LB-IN	155	337	65.00
KDRG2L	Open	LZ	300	361	370	10.15	11.38	8.5	CB	275	LB-IN	155	381	65.00
KDRJ2L	Open	LZ	350	414	500	10	11.31	9.5	CB	500	LB-IN	155	465	70.00
KDRJ1L	Open	LZ	400	477	520	10	11.31	9.5	CB	500	LB-IN	155	470	70.00
KDRL1L	Open	LZ	450	515	610	12.75	14.75	9.25	CB	500	LB-IN	155	509	110.00
KDRL2L	Open	LZ	500	590	610	12.75	14.75	9.25	CB	500	LB-IN	155	518	110.00
KDRL3L	Open	LZ	600	720	720	12.75	15.5	11.5	CB	375	LB-IN	155	748	155.00
KDRS1L	Open	LZ	700	840	840	12.75	15.65	14.25	CB	500	LB-IN	155	872	158.00
KDRX2L	Open	LZ	800	960	965	18.31	18	14.5	CB	275	LB-IN	115	997	160.00
KDRX3L	Open	LZ	900	1080	1080	18.5	18	14.5	CB	275	LB-IN	155	1121	275.00
KDR\X1L	Open	LZ	1000	1200	1200	18.5	18	14.5	CB	375	LB-IN	155	1246	290.00
KDRY1L	Open	LZ	1100	1320	1350	19.5	21	19.25	CB	375	LB-IN	115	1371	475.00
KDRY2L	Open	LZ	1250	1500	1500	19.5	21	19.25	CB	375	LB-IN	155	1558	500.00

\*Ratings and dimensions are equivalent to Part Numbers containing "UL"