

PART NUMBER	ENCL	IMPEDANCE	HORSE POWER	NEC AMPS	MAX CONTINUOUS AMPS	HEIGHT	WIDTH	DEPTH	TERM TYPE	TERM TORQUE	TORQUE UM	TEMP RISE	WATTS LOSS	WEIGHT
KDRA1P	Open	P	2	3.4	4	4	4.18	3.75	TB	10	LB-IN	135	N/A	4.00
KDRA2P	Open	P	3	4.8	6	4	4.18	3.75	TB	10	LB-IN	135	N/A	4.00
KDRA3P	Open	P	5	7.6	8	4	4.18	3.75	TB	10	LB-IN	135	N/A	4.00
KDRA4P	Open	P	7.5	11	12	4	4.18	3.75	TB	10	LB-IN	135	N/A	5.00
KDRB1P	Open	P	10	14	16	5	6	4	TB	20	LB-IN	135	N/A	7.00
KDRD1P	Open	P	15	21	21	6	7.2	4.25	TB	20	LB-IN	135	N/A	10.00
KDRD2P	Open	P	20	27	27	6	7.2	4.25	TB	20	LB-IN	135	N/A	10.00
KDRD3P	Open	P	25	34	35	6	7.2	4.25	TB	20	LB-IN	135	N/A	12.00
KDRD4P	Open	P	30	40	45	6	7.2	4.25	TB	20	LB-IN	135	N/A	12.00
KDRC1P	Open	P	40	52	55	5.75	7.2	5	TB	20	LB-IN	135	N/A	15.00
KDRF1P	Open	P	50	65	80	7	9	6	TB	35	LB-IN	115	N/A	25.00
KDRF2P	Open	P	60	77	80	7	9	6	TB	35	LB-IN	115	N/A	25.00
KDRF3P	Open	P	75	96	110	7	9	6	CB	120	LB-IN	115	N/A	33.00
KDRH1P	Open	P	100	124	130	8.31	10.5	6	CB	120	LB-IN	115	N/A	43.00
KDRI1P	Open	P	125	156	160	8.5	10.5	6.31	CB	275	LB-IN	155	N/A	56.00
KDRI2P	Open	P	150	180	200	8.5	11	7	CB	275	LB-IN	155	N/A	56.00
KDRG1P	Open	P	200	240	250	10.15	11.38	8.25	CB	500	LB-IN	155	N/A	69.00
KDRJ1P	Open	P	250	302	310	10	10.88	9	CB	275	LB-IN	155	N/A	79.00
KDRJ2P	Open	P	300	361	365	10	11.25	9.25	CB	275	LB-IN	155	N/A	79.00
KDRL1P	Open	P	350	414	420	12.75	14.75	9.25	CB	500	LB-IN	155	N/A	95.00
KDRL2P	Open	P	400	477	480	12.75	14.75	9.25	CB	500	LB-IN	155	N/A	104.00
KDRL3P	Open	P	450	515	600	12.75	14.75	9.25	CB	500	LB-IN	155	N/A	109.00
KDLL4P	Open	P	500	590	600	12.75	14.75	9.25	CB	500	LB-IN	155	N/A	109.00

*Ratings and dimensions are equivalent to Part Numbers containing "UL"