

PART NUMBER	ENCL	IMPEDANCE	HORSE POWER	NEC AMPS	MAX CONTINUOUS AMPS	HEIGHT	WIDTH	DEPTH	TERM TYPE	TERM TORQUE	TORQUE UM	TEMP RISE	WATTS LOSS	WEIGHT
KDRA1PE3R	E3R1	P	2	3.4	4	11.5	10	12	TB	10	LB-IN	135	N/A	19.00
KDRA2PE3R	E3R1	P	3	4.8	6	11.5	10	12	TB	10	LB-IN	135	N/A	19.00
KDRA3PE3R	E3R1	P	5	7.6	8	11.5	10	12	TB	10	LB-IN	135	N/A	19.00
KDRA4PE3R	E3R1	P	7.5	11	12	11.5	10	12	TB	10	LB-IN	135	N/A	20.00
KDRB1PE3R	E3R1	P	10	14	16	11.5	10	12	TB	20	LB-IN	135	N/A	22.00
KDRD1PE3R	E3R1	P	15	21	21	11.5	10	12	TB	20	LB-IN	135	N/A	25.00
KDRD2PE3R	E3R1	P	20	27	27	11.5	10	12	TB	20	LB-IN	135	N/A	25.00
KDRD3PE3R	E3R1	P	25	34	35	11.5	10	12	TB	20	LB-IN	135	N/A	27.00
KDRD4PE3R	E3R1	P	30	40	45	11.5	10	12	TB	20	LB-IN	135	N/A	27.00
KDRC1PE3R	E3R1	P	40	52	55	11.5	10	12	TB	20	LB-IN	135	N/A	30.00
KDRF1PE3R	E3R2	P	50	65	80	19.18	15.62	19.5	TB	35	LB-IN	115	N/A	63.00
KDRF2PE3R	E3R2	P	60	77	80	19.18	15.62	19.5	TB	35	LB-IN	115	N/A	63.00
KDRF3PE3R	E3R2	P	75	96	110	19.18	15.62	19.5	PT	120	LB-IN	115	N/A	67.00
KDRH1PE3R	E3R2	P	100	124	130	19.18	15.62	19.5	PT	120	LB-IN	115	N/A	77.00
KDRI1PE3R	E3R2	P	125	156	160	19.18	15.62	19.5	PT	275	LB-IN	155	N/A	95.00
KDRI2PE3R	E3R3	P	150	180	200	22.15	20.62	28.5	PT	275	LB-IN	155	N/A	125.00
KDRG1PE3R	E3R3	P	200	240	250	22.15	20.62	28.5	PT	500	LB-IN	155	N/A	140.00
KDRJ1PE3R	E3R3	P	250	302	310	22.15	20.62	28.5	PT	275	LB-IN	155	N/A	150.00
KDRJ2PE3R	E3R3	P	300	361	365	22.15	20.62	28.5	PT	275	LB-IN	155	N/A	150.00
KDRL1PE3R	E3R3	P	350	414	420	22.15	20.62	28.5	PT	500	LB-IN	155	N/A	168.00
KDRL2PE3R	E3R3	P	400	477	480	22.15	20.62	28.5	PT	500	LB-IN	155	N/A	175.00
KDRL3PE3R	E3R3	P	450	515	600	22.15	20.62	28.5	PT	500	LB-IN	155	N/A	180.00
KDRL4PE3R	E3R3	P	500	590	600	22.15	20.62	28.5	PT	500	LB-IN	155	N/A	180.00

*Ratings and dimensions are equivalent to Part Numbers containing "UL"