

PART NUMBER	ENCL	IMPEDANCE	HORSE POWER	NEC AMPS	MAX CONTINUOUS AMPS	HEIGHT	WIDTH	DEPTH	TERM TYPE	TERM TORQUE	TORQUE UM	TEMP RISE	WATTS LOSS	WEIGHT
KDRMA41H1	Open	HZ	0.25	0.5	0.8	3.63	4.45	1.78	TB	9	LB-IN	135	5.9	1.30
KDRMA42H1	Open	HZ	0.33	0.7	0.75	3.63	4.45	1.78	TB	9	LB-IN	135	9.1	1.20
KDRMA43H1	Open	HZ	0.5	0.9	1.1	3.63	4.45	1.78	TB	9	LB-IN	135	12.9	1.50
KDRMA44H1	Open	HZ	0.75	1.3	1.6	3.63	4.45	1.78	TB	9	LB-IN	135	14.6	1.60
KDRMA45H1	Open	HZ	1	1.7	2.1	3.63	4.45	1.78	TB	9	LB-IN	135	27	1.50
KDRAA46H2	Open	HZ	1.5	2.4	3.2	4.44	4.25	2.64	TB	10	LB-IN	115	26	2.90
KDRAA43H2	Open	HZ	2	2.7	3.4	4.44	4.25	2.64	TB	10	LB-IN	115	23	2.70
KDRAA44H2	Open	HZ	3	3.9	4.5	4.44	4.25	2.64	TB	10	LB-IN	115	34	2.90
KDRAA57H2	Open	HZ	4	4.9	6	4.44	4.25	2.64	TB	10	LB-IN	115	47.9	3.50
KDRAA58H2	Open	HZ	5	6.1	6.8	4.44	4.25	2.64	TB	10	LB-IN	115	43.7	3.40
KDRULB42H	Open	HZ	7.5	9	10	5	6	4	TB	20	LB-IN	115	61	8.00
KDRULB43H	Open	HZ	10	11	11	5	6	4	TB	20	LB-IN	115	70	8.00
KDRULB44H	Open	HZ	15	17	18.5	5	6	4	TB	20	LB-IN	115	73	8.00
KDRULD41H	Open	HZ	20	22	23	5.75	7.2	4.25	TB	20	LB-IN	115	105	12.00
KDRULC43H	Open	HZ	25	27	30	5.75	7.2	5	TB	20	LB-IN	115	107	15.00
KDRULE42H	Open	HZ	30	32	32	5.75	7.2	5	TB	20	LB-IN	115	140	16.00
KDRULF44H	Open	HZ	40	41	44	7	9	6	TB	35	LB-IN	115	172	30.00
KDRULF45H	Open	HZ	50	52	58	7	9	6	TB	35	LB-IN	115	165	30.00
KDRULH43H	Open	HZ	60	62	62	9	11	6	TB	35	LB-IN	115	205	45.00
KDRULH42H	Open	HZ	75	77	82	9	11	6	TB	35	LB-IN	115	251	45.00
KDRULI41H	Open	HZ	100	99	99	9	11	7.25	PT	120	LB-IN	155	268	53.00
KDRULG44H	Open	HZ	125	125	130	9	11	8	PT	120	LB-IN	155	381	68.00
KDRULG45H	Open	HZ	150	144	155	9	11	8.12	PT	275	LB-IN	155	405	71.00
KDRULJ41H	Open	HZ	200	192	192	9	11	9.25	PT	275	LB-IN	155	466	76.00
KDRULL46H	Open	HZ	250	242	260	11.38	15	11.25	PT	500	LB-IN	155	478	120.00
KDRULL47H	Open	HZ	300	289	310	11.38	15	12	PT	275	LB-IN	155	490	120.00
KDRULL48H	Open	HZ	350	336	344	11.38	15	11.75	PT	275	LB-IN	155	539	120.00
KDRULL49H	Open	HZ	400	382	382	11.38	15	11.75	PT	275	LB-IN	155	603	120.00
KDRULS47H	Open	HZ	450	412	440	11.38	15	13.25	PT	500	LB-IN	155	521	175.00
KDRULS46H	Open	HZ	500	472	500	11.38	15	13.25	PT	500	LB-IN	155	660	175.00
KDRULS49H	Open	HZ	600	576	576	11.38	15.5	13.25	PT	375	LB-IN	155	1194	187.00
KDRULX45H	Open	HZ	700	672	760	18.5	21	18	PT	375	LB-IN	155	1393	215.00
KDRULX44H	Open	HZ	800	768	850	18.5	21	18	PT	375	LB-IN	155	1592	298.00
KDRULX41H	Open	HZ	900	864	900	18.5	21	18	PT	375	LB-IN	155	1791	308.00
KDRULX42H	Open	HZ	1000	960	1000	18.5	21	18	PT	275	LB-IN	155	1990	393.00
KDRULX43H	Open	HZ	1100	1056	1064	18.5	21	18	PT	375	LB-IN	155	2189	468.00
KDRULY41H	Open	HZ	1250	1200	1200	20	23	23	PT	375	LB-IN	155	2488	505.00
KDRULY42H	Open	HZ	1500	1440	1500	20	23	23	PT	375	LB-IN	155	2985	600.00