



Technical data and measuring conditions.

Rated Voltage $V_R$	760/440 V AC, 50/60Hz.			
Rated Current $I_R$	Referred to 40 °C ambient temperature			
Test Voltage $V_{test}$	3270 V DC, 2 s (line/line) 2890 V DC, 2 s (line/case)			
Overload Capability (thermal)	1.5 · $I_R$ for 3 min per hour or 2.5 · $I_R$ for 30 s per hour			
Leakage Current $I_{leak}$	At 760 V AC, 50 Hz.			
Climatic Category (IEC 60068-1)	25/100/21 (-25 °C/+100 °C/21 days damp heat test)			
Approval Standards	EN 133200, UL 1283, CSA C22.2 No. 8			
Approval Markings	UR, cUR			

$V_R$	$I_R$	$I_{leak}$	$R_{typ.}$	Approx. Weight
AC	A	mA	$\mu$ ohm	kg. / lbs.
760/440	150	< 28	140	13 / 28.6

			TOLERANCES (EXCEPT AS NOTED)		W132 N10611 Grant Drive Germantown, WI 53022
			DECIMAL		
			.XX ± .02		<b>KRF FILTER</b> <b>KRF0150VCB, 600-690V, 150A</b>
			.XXX ± .01		
ECO 3959 ADDED	4/24/17	JRN	FRACTIONAL ± 1/32		DRN BY DSW
APPROVAL MARKINGS			ANGULAR ± 1/2°		DATE 1/06/2010
NO	REVISION	DATE	BY	SCALE TO FIT	DWG. NO. KRF0150VCB
					SHT.1 OF1