



NOTE: FOR WIRE RANGE AND TORQUE INFORMATION SEE IOM MANUAL.

MSD PART NUMBER	HP	VOLTAGE	CURRENT	WEIGHT	TERMINAL BLOCK	GROUND LUG
MSD0005A300	3	480V	5 AMPS	57LBS	WIRE RANGE: 1-22AWG	WIRE RANGE: 1/0 -14AWG
MSD0009A300	5	480V	9 AMPS	57LBS	WIRE RANGE: 1-22AWG	WIRE RANGE: 1/0 -14AWG
MSD0012A300	7.5	480V	12 AMPS	58LBS	WIRE RANGE: 1-22AWG	WIRE RANGE: 1/0 -14AWG
MSD0016A300	10	480V	16 AMPS	58LBS	WIRE RANGE: 1-22AWG	WIRE RANGE: 1/0 -14AWG

CUSTOMER IS RESPONSIBLE FOR INSTALLATION TO MEET ALL NATIONAL AND LOCAL ELECTRICAL CODES.

NO	REVISION	DATE	BY	TOLERANCES (EXCEPT AS NOTED)	DECIMAL	ANGULAR
G	4095 ADDED MSD0005A300	8/18/17	JRN	XX	+/- .25	
F	3696 ADD DISCHARGE LABEL	7/29/16	DSW	.XXX	+/- .1	
E	3345 ENCLOSURE UPDATED	9/4/2015	DSW	+/-	1/16	
D	3364, 75°C TO 90°C MIN	6/30/2015	DSW			1°
C	3308 ADD CUSTOMER ENTRANCE	5/19/15	DSW			

JRN BY	DATE	DWG. No.
DSW	12/17/14	105794DG
SCALE	APRVD.	SHEET 1 OF 1
1/3		

TCI® W132 N10611 Grant Drive
Germantown, WI 53022

MSD 9 AMPS TO 16 AMPS
MotorShield Sinewave Filter
480/3/60, Type 1/ 3R.